



REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2012/04/13

Specifications:

Electrical:

- 1.Current Rating
2.0A/contact terminal
- 2.Voltage Rating
30V DC
- 3.Contact Resistance
30 milliohms MAX
- 4.Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 5.Insulation Resistance:
1000MEGA ohms MIN

Mechanical:

- 1.Connector Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
- 2.Terminal Retention
1.2kgf(MIN)

Material:

- 1.Housing:
Hing Temperature Thermoplastics,
UL 94V-0 PBT White/Black
- 2.Contact:Copper Alloy C2680
- 3.Shell: Copper Alloy C2680/SPCC

Finish:

- 1.Contact: Plated Gold in Mating Area;
Tin Sn Solder Tails
- 2.Shell:
Nickel Plating

GENERAL TOLERANCE		DWG NO.	Title		Part NO.
X±0.45	X±.15'	JYSA0804-001	USB A/F 90° DIP短体(10.00)		
X±0.35	X±.2'				
XX±0.25	.XX±.1'		JYS-USB630-012		
.XXX±0.15	.xxx±0.5'				
SHEET	1/1				
		APPD:	WIND	Scale	1:1
		CHKD:		UNIT	mm
		DR:			
		Date	2012/04/13		

杰宇森电子有限公司
JIE YU SEN ELECTRONIC CO., LTD.