



规格说明 Specifications:
电气特性 Electrical:

- 1. 额定电流: Current Rating 1.8A/contact terminal
- 2. 额定电压: Voltage Rating 30V DC
- 3. 接触电阻: Contact Resistance 50 milliohms MAX
- 4. 绝缘电压: Dielectric Withstanding Voltage: 300 V AC AT Sea Level
- 5. 绝缘电阻: Insulation Resistance: 100MEGA ohms MIN

物理性能 Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force Mate force: 3.0kgf(MAX) Unmate force: 0.7kgf(MIN)
- 2. 机械寿命: 5000次

原材料 Material:

- 1. 塑胶 Housing: Hing Temperature Thermoplastics UL 94V-0 LCP Black
- 2. 端子材料: Contact: C5191 EH
- 3. 外壳: Shell: H65 EH

电镀 Finish:

- 1. 端子: Contact: Plated Gold in Mating Area; Tin On Solder Tails
- 2. 外壳: Shell: Nickel Plating (电镀前自上线)

GENERAL TOLERANCE	DWG NO.	APPD:	WIND	Scale
X.±0.45	JYSA0909-001	CHKD:		1:1
X.±0.35		DR:		mm
XX±0.25		Date	2011/10/31	
XXX±0.15				

REV.	EQN. NO.	MODIFY CONTENT	DATE
A		NEW	2011/10/31

		深圳市杰宇森电子有限公司 Shenzhen JieYuSen electronic co., LTD.
--	--	--