



RECOMMENDED PCB LAYOUT

TOL: (±0.05)

JYS-BY150-116	0.80	0.80
JYS-BY150-117	1.00	1.00
P/N	DIM A (mm)	DIM B (mm)

- NOTES-
- 1.Electrical:
 - Contact resistance: 50m ohms max.
 - Dielectric withstanding voltage: 250V RMS.
 - Insulation resistance: 1000M ohms min.
 - 2.Mechanical:
 - MATE AND UNMATE FORCE:
 - MATE FORCE: 2kg MAX
 - UNMATE FORCE: 0.3kg MIN
 - Durability: 3000cycles MIN.
 - 3.Environment:
 - Operating Temperature: -55to+105;
 - 4.FINISH:
 - TERMINAL: GOLD Plated ALL Over NICKEL.
 - 5.COLOR:
 - HOUSING: BLACK.

GENERAL TOLERANCE		DWG NO.	APPD:		WMD	Scale
X:±0.45	X:±5°	JYSA1126-02	CHKD:			1:1
.X±0.35	.X'±2°	BATTERY 3PIN 3.0PITCH	DR:			mm
.XX±0.25	.XX'±1°	标题 端子标题	Date	2015/03/29		
.XXX±0.15	.xxx'±0.5°	Part NO.				
SHEET 1/1						



杰宇森电子有限公司
JIE YU SEN ELECTRONIC CO., LTD.