



RECOMMENDED PCB LAYOUT(TOP VIEW)
GENERAL TOLERANCES:±0.05

NOTE:

1. MATERIAL:
HOUSING: THERMOPLASTIC/BLACK/JUL 94V-0
CONTACT: COPPER ALLOY.
2. FINISH:
CONTACT:GOLD PLATING 1u"Min. PLATED OVER NICKEL
- 3.SPECIFICATION:
1. CONTACT CURRENT RATING: 1A.
2. CONTACT RESISTANCE: 30 mΩ MAX.;
3. INSULATION RESISTANCE: 100MΩ MIN.;
4. DIELECTRIC WITHSTANDING: 500V AC MIN.;
5. DURABILITY: 5,000 CYCLES MIN.;
6. CONNECTOR MATING FORCES: 29.4N (3.00Kgf) MAX.;
7. CONNECTOR UNMATING FORCES: 2.94N(0.30Kgf) MIN.;
8. OPERATING TEMPERATURE: -25° TO +85°

P5	DETECT
P4	LFT
P3	RT
P2	MIC
P1	GND
PIN NO.	NAME

PART NAME	Q'ty	MATERIAL	DESCRIPTION	REMARK
CONTACT 5	1	COPPER ALLOY	GOLD PLATING 1u"Min./SOLDER AREA PLATED OVER NICKEL	T=0.15
CONTACT 4	1	COPPER ALLOY	GOLD PLATING 1u"Min./SOLDER AREA PLATED OVER NICKEL	T=0.15
CONTACT 3	1	COPPER ALLOY	GOLD PLATING 1u"Min./SOLDER AREA PLATED OVER NICKEL	T=0.20
CONTACT 2	1	COPPER ALLOY	GOLD PLATING 1u"Min./SOLDER AREA PLATED OVER NICKEL	T=0.20
CONTACT 1	1	COPPER ALLOY	GOLD PLATING 1u"Min./SOLDER AREA PLATED OVER NICKEL	T=0.15
HOUSING	1	THERMOPLASTIC	BLACK UL 94V-0	

GENERAL TOLERANCE	DWG NO.	APPD:	WMD	Scale
X:±0.45	JYSA0528-001	CHKD:		1:1
X±0.35				
.XX±0.25	H36 耳机座 6DIP 间距1.4mm	DR:		
.XXX±0.15				
	JYS-JK360-025	Date	2012/04/10	
SHEET 1/1				



杰宇森电子有限公司
JIE YU SEN ELECTRONIC CO., LTD.

REV.	EGN.NO.	MODIFY CONTENT	DATE
A		NEW	2012/04/10